

ISO Proof Coil Chain - G30 General Purpose/Anchor Chain



ISO Proof Coil Chain is low carbon steel general purpose/anchor chain with an ISO short pitch link. It is used in applications where high tensile strength is not required.

Finish: Hot Dip Galvanized

Packaging: Full Drums, Half Drums, and Pails

| Trade Size in. | Wire Diameter | | Inside Dimensions | | | | Working Load Limit | |
|-------------------|---------------|-------|-------------------|------|-------|------|-----------------------|-----------------|
| | mm | in. | Length | | Width | | kg-force | pound- force |
| | | | mm | in. | mm | in. | | |
| 3/16 | 5.5 | 0.218 | 24.64 | 0.97 | 10.16 | 0.4 | 363 | 800 |
| 1/4 | 7 | 0.276 | 25.4 | 1.00 | 12.7 | 0.5 | 590 | 1300 |
| 5/16 | 8.4 | 0.329 | 28.45 | 1.12 | 12.7 | 0.5 | 862 | 1900 |
| 3/8 | 10 | 0.394 | 31.24 | 1.23 | 15.75 | 0.62 | 1202 | 2650 |
| 1/2 | 13 | 0.519 | 38.1 | 1.50 | 20.57 | 0.81 | 2041 | 4500 |
| 5/8 | 16 | 0.630 | 48.26 | 1.90 | 25.65 | 1.01 | 3130 | 6900 |
| 3/4 | 20 | 0.781 | 55.88 | 2.20 | 27.69 | 1.09 | 4808 | 10600 |

| Trade size in. | Plastic Pail | | | | | Half Drum | | | | | Full Drum | | | | |
|----------------------|--------------|-----|--------|-----|--------------------|-----------|-----|--------|-----|--------------------|-----------|-----|--------|------|---------------------|
| | Weight | | Length | | Part ID | Weight | | Length | | Part ID | Weight | | Length | | Part ID |
| | kg | lbs | m | ft. | | kg | lbs | m | ft. | | kg | lbs | m | ft. | |
| 3/16 | 47 | 102 | 76.2 | 250 | CHG3001875I-SOX250 | 148 | 327 | 243.84 | 800 | CHG3001875I-SOX800 | 297 | 654 | 487.68 | 1600 | CHG3001875I-SOX1600 |
| 1/4 | 46 | 101 | 42.98 | 141 | CHG30025ISOX141 | 130 | 287 | 121.92 | 400 | CHG30025ISOX400 | 260 | 574 | 243.84 | 800 | CHG30025ISOX800 |
| 5/16 | 43 | 95 | 28.04 | 92 | CHG3003125I-SOX92 | 129 | 284 | 83.82 | 275 | CHG3003125I-SOX275 | 258 | 568 | 167.64 | 550 | CHG3003125ISOX550 |
| 3/8 | 44 | 96 | 19.2 | 63 | CHG300375ISOX63 | 138 | 305 | 60.96 | 200 | CHG300375ISOX200 | 277 | 611 | 121.92 | 400 | CHG300375ISOX400 |
| 1/2 | 44 | 96 | 10.97 | 36 | CHG3005ISOX36 | 121 | 266 | 30.48 | 100 | CHG3005ISOX100 | 241 | 531 | 60.96 | 200 | CHG3005ISOX200 |
| 5/8 | - | - | - | - | - | - | - | - | - | - | 264 | 582 | 45.72 | 150 | CHG300625ISOX150 |
| 3/4 | - | - | - | - | - | - | - | - | - | - | 261 | 576 | 30.48 | 100 | CHG30075ISOX100 |

Please see page 3 for packaging details.

Warning: Working Load Limit must not be exceeded. Not to be used for lifting or hoisting applications